

ez_trans_prop

- Description
- Prototype and Arguments
 - Main language use
- Usage

>= 5.4 / 2014.09

Description

`ez_trans_prop()` is a generic, low level Twig helper which correct translated value of a multi valued(translations) property.

If the current language cannot be found as a translation for content, main language (see [further down for details](#)) will be used if this is supported by provided **object**. This behavior is identical when forcing a language using **forcedLanguage**.

Prototype and Arguments

`ez_trans_prop(ValueObject object, string property[, string forcedLanguage])`

Argument name	Type	Description
<code>object</code>	<code>eZ\Publish\Core\Repository\Values\ValueObject</code>	ValueObject object property belongs to.
<code>property</code>	<code>string</code>	Property to get translated value from, logic is using one of the following (in this order): <ul style="list-style-type: none">▪ <code>property "{property}s"</code>▪ <code>method "get{property}"</code>
<code>forcedLanguage</code>	<code>string</code>	Language we want to force (e.g. "eng-US"), otherwise takes prioritized languages from SiteAccess settings.

Main language use

Main language is attempted to be applied in the following way for Value objects that support this:

- *property*: Use **mainLanguageCode** property if it exists, but not if **alwaysAvailable** exists and is true
- *method*: Provide `$language = null` as only argument to method, depends on logic of ValueObject if this gives a fallback value or not

Usage

Example below shows how this function can be used to get the Content name with exact same result as using `ez_content_name(content)`

```
<span>{{ ez_trans_prop( versionInfo, "name" ) }}</span>
```