

# Recommendation Bundle

The Recommendation Bundle extends the functionality of eZ Publish with a recommendation engine, powered by [YOOCHOOSE](#). It allows you to track the way visitors use your website and suggests recommended content to them based on their behavior.

See <https://yoochoose.com/Personalization-Solution/Documentation> to learn how the recommendation engine works from the YOOCHOOSE side.

## Installing the Recommendation Bundle

The Recommendation Bundle is installed in a similar way as any other Symfony bundle.

### Requirements

- PHP 5.4.4 or higher PHP 5.x version
- Symfony 2.7 or higher Symfony 2.x version
- eZ Publish Platform 5.4.5 or above, with the REST API configured to use sessions and publicly open to the YOOCHOOSE servers
- A YOOCHOOSE license

This bundle is independent from the `ezrecommendation` extension used in legacy, and does not require it.

### Step 1: Installation

1. Run the following from your eZ Publish installation root (*here with most recent 1.x release*):

```
composer require --no-update
ezsystems/recommendation-bundle:^1.0.0
composer update --prefer-dist
```

2. Enable the bundle in `ezpublish/EzPublishKernel.php`:

```
$bundles = array(
    // existing bundles
    new
    EzSystems\RecommendationBundle\EzSystemsRecommendationBu
    ndle()
);
```

3. Import additional routing by adding following lines to your `routing.yml` file:

```
recommendationBundleRestRoutes:
    resource:
"@EzSystemsRecommendationBundle/Resources/config/routing
_rest.yml"
    prefix:    %ezpublish_rest.path_prefix%
```

Keep in mind that legacy support is disabled by default. To enable legacy search engine (requires `ezpublish-kernel` bundle) uncomment these lines in the bundle's `services.yml`:

### In this topic:

- Installing the Recommendation Bundle
  - Requirements
  - Step 1: Installation
  - Step 2: Configuration
    - Advanced configuration
  - Step 3: Clear prod cache
- Using the Recommendation Bundle
  - Initial Setup
  - Indexing
  - Tracking
  - Displaying
  - Troubleshooting

### Further information:

[API doc for YOOCHOOSE Service](#)

[Developer Guides for YOOCHOOSE Service](#)

```

# ez_recommendation.legacy.search_engine:
#   class: ezpSearchEngine
#   factory_class:
EzSystems\RecommendationBundle\ez\Publish\LegacySearch\L
egacySearchFactory
#   factory_method: build
#   arguments: [@ezpublish_legacy.kernel]

# ez_recommendation.legacy.recommendation_search_engine:
#   class:
EzSystems\RecommendationBundle\ez\Publish\LegacySearch\R
ecommendationLegacySearchEngine
#   arguments:
#     - @ez_recommendation.client.yoochoose_notifier
#     - @ez_recommendation.legacy.search_engine

# ez_recommendation.legacy.search_configuration_mapper:
#   class:
EzSystems\RecommendationBundle\ez\Publish\LegacySearch\C
onfigurationMapper
#   arguments:
#     -
@ez_recommendation.legacy.recommendation_search_engine
#     - @ezpublish.siteaccess
#   tags:
#     - { name: kernel.event_subscriber }

```

## Step 2: Configuration

The bundle's configuration is siteaccess-aware. This is an example of settings (*config.yml*):

```

ez_recommendation:
  system:
    default:
      yoochoose:
        customer_id: "12345"
        license_key: "1234-5678-9012-3456-7890"
        server_uri: "http://example.com"
      recommender:
        included_content_types: ["blog",
"article"]

```

The following parameters need to be included in the settings file:

Parameter	Description
yoochoose.customer_id	Your YOOCHOOSE customer ID.
yoochoose.license_key	Your YOOCHOOSE license key.
server_uri	The URI your site's REST API can be accessed from.

recommender.included_content_types	Content Types on which the tracking script will be shown. See <a href="#">Tracking</a> below for more information.
------------------------------------	--

If content's author or image are stored in different field, you can specify it in **parameters.yml**:

### Format

```
ez_recommendation.field_identifiers:
    {field fetched by controller (image or author)}
    {content type}: {field with value}
```

For example:

### Actual example

```
ez_recommendation.field_identifiers:
    author:
        article: authors
    image:
        article: thumbnail
        blog_post: main_image
```

## Advanced configuration

You can select advanced options for YOOCHOOSE back end using the following settings:

```
ez_recommendation:
    api_endpoint: 'https://admin.yoochoose.net'
    recommender:
        api_endpoint: 'http://reco.yoochoose.net'
        consume_timeout: 20
    tracking:
        api_endpoint: 'http://event.yoochoose.net'
        script_url: 'cdn.yoochoose.net/yct.js'
```

Changing any of these parameters without a valid reason will break all calls to YOOCHOOSE. It can be useful to test the API by mocking the service, or if you have a hosted version of YOOCHOOSE Recommendation service.

## Step 3: Clear prod cache

While Symfony dev environment keeps track of changes to yml files, prod does not, so to make sure Symfony reads the new config we clear cache:

```
php app/console --env=prod clear:cache
```

## Using the Recommendation Bundle

## Initial Setup

Your content structure must be mapped to the YOOCHOOSE domain model. This must be done in collaboration with YOOCHOOSE.

## Indexing

**Public** content is automatically indexed. When necessary, eZ Publish will notify YOOCHOOSE of changes to content. Initial import is to be managed with your YOOCHOOSE sales representative. Note that your server's REST API will need to be open to the YOOCHOOSE servers for indexing to be possible.

## Tracking

Events from the site need to be sent to YOOCHOOSE so that recommendations can be adapted to visitors. Tracking can be set up in multiple ways, depending on existing constraints.

`EzSystemsRecommendationBundle` delivers a Twig extension which helps integrate the tracking functionality into your site.

### To enable tracking

1. Place the following snippet of code somewhere in the HEAD section of your header template:

```
{% if content is defined %}
    {{ yc_track_user(content.id) }}
{% endif %}
```

2. Configure settings under the `recommender.included_content_types` parameter (see the `default_settings.yml` file delivered with this bundle). Here you can define for which Content Types tracking script will be shown.

In the YOOCHOOSE documentation you can find more information about [tracking in general](#) and about the [generic asynchronous javascript tracker](#).

Additionally, in case of missing content owner Id, there's an option in `default_settings.yml` to set up the default content author:

```
ez_recommendation.default.author_id: 14 # ID: 14 is
default ID of admin user
```

## Displaying

In order to allow displaying recommendations on your site you must add portions of scripts which will integrate the recommender engine with your site.

Implementation is very easy and can be performed in just a few steps (assuming that the `EzSystemsRecommendationBundle` is properly configured and enabled in `EzPublishKernel.php`):

### To enable displaying recommendations

1. Add the following JavaScript assets to your header template:

```

{% javascripts
  ...

  '%kernel.root_dir%/../vendor/components/handlebars.js/handlebars.min.js'

  '@EzSystemsRecommendationBundle/Resources/public/js/recommendationtemplaterenderer.js'

  '@EzSystemsRecommendationBundle/Resources/public/js/recommendationtemplatehelper.js'

  '@EzSystemsRecommendationBundle/Resources/public/js/recommendationrestclient.js'
%}

```

2. Place a dedicated Twig helper in the place where you want to display recommendations:

```

{{ yc_show_recommendations(
  contentId = content.id,
  scenario = '',
  limit = '',
  contentType = '',
  template = '',
  fields = []
) }}

```

## Parameters

Parameter	Type	Description
contentId	int	In content-based views the Twig variable holding the content id (the content you want to get recommendations for).
scenario	string	Scenario used to display recommendations. You can create custom scenarios at the YOOCHOOSE dashboard.
limit	int	Number of recommendations to show.
contentType	string	Content Types you are expecting in response.
template	string	HandleBars template name (your templates are stored in the <code>ezsystems/recommendation-bundle/Resources/public/views</code> directory. Take a look at <code>default.html.twig</code> which includes a default template that can be used to prepare customized versions).

fields	array	Fields which are required and will be requested from the recommender engine. These field names are also used inside HandleBars templates.
--------	-------	---

Sample integration can take the following form:

```
{{ yc_show_recommendations(
  contentId = content.id,
  scenario = 'popular',
  limit = 5,
  contentType = 'article',
  template = 'default',
  fields = ['ez_publishedDate', 'ez_url',
'title', 'image', 'author', 'intro']
) }}
```

You can also bypass named arguments using standard value passing as arguments.

## Item ID

The item id is usually set to the viewed ContentId. Depending on requirements, it can be set to a different value, in collaboration with YOOCHOOSE.

## Displaying image aliases

Displaying image variations defined with image aliases is not currently supported out of the box.

You can work around this limitation by creating your own template (based on <https://github.com/ezsystems/ezstudio-demo/blob/master/app/Resources/EzSystemsRecommendationBundle/views/recommendations.html.twig>) or your own Twig extension (based on <https://github.com/ezsystems/EzSystemsRecommendationBundle/blob/master/Twig/RecommendationTwigExtension.php#L214>).

If you want to access a specific image alias through API, you need to add the `image` parameter to the request url with name of alias as its value, for example:

```
/api/ezp/v2/ez_recommendation/v1/contenttypes/16?lang=eng-GB&fields=title,description,image,intro,name&page=1&page_size=20&image=rss
```

to retrieve the `rss` alias of the image.

### V1.1

As of v1.1 of the bundle, one more parameter is available: `sa`, which takes the siteaccess name and defines the siteaccess whose content will be displayed.

## Troubleshooting

Most operations are logged via the `ez_recommendation` [Monolog channel](#). To log everything about Recommendation to `dev.recommendation.log`, add the following to your `config.yml`:

```
monolog:
  handlers:
    ez_recommendation:
      type: stream
      path:
"%kernel.logs_dir%/%kernel.environment%.recommendation.log"
      channels: [ez_recommendation]
      level: info
```

You can replace `info` with `debug` for more verbosity.